



- ↳ Hybrid SAD-GDT Technology
- ↳ UL497B LISTED
- ↳ 20kA I_{max} (1x 8/20us)
- ↳ 5kA I_{mp} (2x 10/350us)
- ↳ 5kA I_n (10x 8/20us)
- ↳ Modular
- ↳ 2W+SHIELD+G

	Electrical Characteristics																																																													
<p>G: 3-electrode gas tube Gb: 2-electrode gas tube R: Resistor D: Clamping diode</p>	<table border="1"> <tr> <td>Network</td> <td></td> <td>RNIS-T0, 48 V line</td> </tr> <tr> <td>Max. DC operating voltage</td> <td>U_c</td> <td>53 Vdc</td> </tr> <tr> <td>Max. frequency</td> <td>f max.</td> <td>> 3 MHz</td> </tr> <tr> <td>Insertion loss</td> <td></td> <td>< 1 dB</td> </tr> <tr> <td>Max. load current @25°C</td> <td>IL</td> <td>300 mA</td> </tr> <tr> <td>Impulse current 2 x 10/350µs Test - D1 Category</td> <td>I_{imp}</td> <td>5 kA</td> </tr> <tr> <td>Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category</td> <td>I_n L/PE</td> <td>5 kA</td> </tr> <tr> <td>DATA SPD TYPE</td> <td></td> <td>UL497B LISTED</td> </tr> <tr> <td>VOLTS</td> <td>(V)</td> <td>48</td> </tr> <tr> <td>WIRES</td> <td></td> <td>2W+SHIELD+G</td> </tr> <tr> <td>LINE CURRENT MAX</td> <td>(A)</td> <td>0.3</td> </tr> <tr> <td>AMBIENT MIN</td> <td>(C)</td> <td>-50</td> </tr> <tr> <td>AMBIENT MAX</td> <td>(C)</td> <td>+85</td> </tr> <tr> <td>RESIDUAL VOLTAGE</td> <td>(V)</td> <td>70</td> </tr> <tr> <td>MCOV</td> <td>(V)</td> <td>60</td> </tr> <tr> <td>I_N 10 impulses 8/20µs</td> <td>(kA)</td> <td>5</td> </tr> <tr> <td>I_{MAX} 8/20µs</td> <td>(kA)</td> <td>20</td> </tr> <tr> <td>I_{imp} 10/350µs</td> <td>(kA)</td> <td>5</td> </tr> <tr> <td>DATA SPEED</td> <td>(Mbps)</td> <td>10/100</td> </tr> <tr> <td>INSERTION LOSS (@ FREQ)</td> <td>(db)</td> <td>< 1</td> </tr> </table>		Network		RNIS-T0, 48 V line	Max. DC operating voltage	U _c	53 Vdc	Max. frequency	f max.	> 3 MHz	Insertion loss		< 1 dB	Max. load current @25°C	IL	300 mA	Impulse current 2 x 10/350µs Test - D1 Category	I _{imp}	5 kA	Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	I _n L/PE	5 kA	DATA SPD TYPE		UL497B LISTED	VOLTS	(V)	48	WIRES		2W+SHIELD+G	LINE CURRENT MAX	(A)	0.3	AMBIENT MIN	(C)	-50	AMBIENT MAX	(C)	+85	RESIDUAL VOLTAGE	(V)	70	MCOV	(V)	60	I _N 10 impulses 8/20µs	(kA)	5	I _{MAX} 8/20µs	(kA)	20	I _{imp} 10/350µs	(kA)	5	DATA SPEED	(Mbps)	10/100	INSERTION LOSS (@ FREQ)	(db)	< 1
Network		RNIS-T0, 48 V line																																																												
Max. DC operating voltage	U _c	53 Vdc																																																												
Max. frequency	f max.	> 3 MHz																																																												
Insertion loss		< 1 dB																																																												
Max. load current @25°C	IL	300 mA																																																												
Impulse current 2 x 10/350µs Test - D1 Category	I _{imp}	5 kA																																																												
Nominal Discharge Current, X-C (Line/Earth) 8/20µs Test x 10 - C2 Category	I _n L/PE	5 kA																																																												
DATA SPD TYPE		UL497B LISTED																																																												
VOLTS	(V)	48																																																												
WIRES		2W+SHIELD+G																																																												
LINE CURRENT MAX	(A)	0.3																																																												
AMBIENT MIN	(C)	-50																																																												
AMBIENT MAX	(C)	+85																																																												
RESIDUAL VOLTAGE	(V)	70																																																												
MCOV	(V)	60																																																												
I _N 10 impulses 8/20µs	(kA)	5																																																												
I _{MAX} 8/20µs	(kA)	20																																																												
I _{imp} 10/350µs	(kA)	5																																																												
DATA SPEED	(Mbps)	10/100																																																												
INSERTION LOSS (@ FREQ)	(db)	< 1																																																												
	Mechanical Characteristics																																																													
	<table border="1"> <tr> <td>Technology</td> <td colspan="2">GDT+Clamping diode</td> </tr> <tr> <td>Connection to Network</td> <td colspan="2">By screw terminal: cross section 0.5-2.5mm²</td> </tr> <tr> <td>Format</td> <td colspan="2">Plug-in DIN box</td> </tr> <tr> <td>Failsafe mode</td> <td colspan="2">Short-circuit</td> </tr> <tr> <td>With line cut-off in case of removal plug-in module</td> <td colspan="2">Yes</td> </tr> <tr> <td>TECHNOLOGY</td> <td colspan="2">SAD-GDT</td> </tr> <tr> <td>NETWORK CONFIGURATION</td> <td colspan="2">1 pair</td> </tr> <tr> <td>CONNECTION METHOD</td> <td colspan="2">Screw Terminal</td> </tr> <tr> <td>DISCONNECTION</td> <td colspan="2">Line disconnect with module removal</td> </tr> <tr> <td>MOUNTING</td> <td colspan="2">DIN RAIL</td> </tr> <tr> <td>MATERIAL</td> <td colspan="2">Thermoplastic UL94-V0</td> </tr> <tr> <td>NEMA RATING (IP RATING)</td> <td colspan="2">NEMA 2 (IP20)</td> </tr> <tr> <td>DIMENSIONS</td> <td colspan="2">See diagram</td> </tr> <tr> <td>WEIGHT</td> <td colspan="2">0.30 lbs</td> </tr> <tr> <td>SPARE PART</td> <td colspan="2">DLAWM-48D3</td> </tr> </table>		Technology	GDT+Clamping diode		Connection to Network	By screw terminal: cross section 0.5-2.5mm ²		Format	Plug-in DIN box		Failsafe mode	Short-circuit		With line cut-off in case of removal plug-in module	Yes		TECHNOLOGY	SAD-GDT		NETWORK CONFIGURATION	1 pair		CONNECTION METHOD	Screw Terminal		DISCONNECTION	Line disconnect with module removal		MOUNTING	DIN RAIL		MATERIAL	Thermoplastic UL94-V0		NEMA RATING (IP RATING)	NEMA 2 (IP20)		DIMENSIONS	See diagram		WEIGHT	0.30 lbs		SPARE PART	DLAWM-48D3																
Technology	GDT+Clamping diode																																																													
Connection to Network	By screw terminal: cross section 0.5-2.5mm ²																																																													
Format	Plug-in DIN box																																																													
Failsafe mode	Short-circuit																																																													
With line cut-off in case of removal plug-in module	Yes																																																													
TECHNOLOGY	SAD-GDT																																																													
NETWORK CONFIGURATION	1 pair																																																													
CONNECTION METHOD	Screw Terminal																																																													
DISCONNECTION	Line disconnect with module removal																																																													
MOUNTING	DIN RAIL																																																													
MATERIAL	Thermoplastic UL94-V0																																																													
NEMA RATING (IP RATING)	NEMA 2 (IP20)																																																													
DIMENSIONS	See diagram																																																													
WEIGHT	0.30 lbs																																																													
SPARE PART	DLAWM-48D3																																																													
	Standards																																																													
	<table border="1"> <tr> <td>UL STANDARD</td> <td colspan="2">UL497B</td> </tr> <tr> <td>UL CATEGORY</td> <td colspan="2">QVQG</td> </tr> <tr> <td>UL FILE NUMBER</td> <td colspan="2">E184939</td> </tr> <tr> <td>STANDARDS</td> <td colspan="2">IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993</td> </tr> <tr> <td>ENVIRONMENTAL STANDARDS</td> <td colspan="2">ROHS</td> </tr> </table>		UL STANDARD	UL497B		UL CATEGORY	QVQG		UL FILE NUMBER	E184939		STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993		ENVIRONMENTAL STANDARDS	ROHS																																														
UL STANDARD	UL497B																																																													
UL CATEGORY	QVQG																																																													
UL FILE NUMBER	E184939																																																													
STANDARDS	IEC 61643-11, NOM-003-SCFI-2014, NOM-001-SCFI-1993																																																													
ENVIRONMENTAL STANDARDS	ROHS																																																													
	Part number																																																													
	640804																																																													

